



SANTAK BLAZER SERIES LINE-INTERACTIVE UPS

BLAZER Pro series

1200VA / 2200VA



Ideal for protecting:

- PC, workstations
- NAS, Network equipment
- POS, ATM, KIOSKS
- Critical electronic devices



AUTHORIZED DISTRIBUTOR OF SANTAK UPS PRODUCTS IN VIET NAM
ECOTEK CANADA PROMOTION TRADE CORPORATION

REGISTERED ADDRESS:

1188 West Georgia Street, Unit 1440, Vancouver, B.C, Canada, V6E 4A2
Co. Reg. No.: BC0895460
Web : www.ecotek-canada.vn



CONTACTS IN VIETNAM:

3/4 Nguyen Van Thu Str, Da Kao ward, District 1, Ho Chi Minh City, Vietnam

Phone : +84-904.204.849 (The **North** of Vietnam)

: +84-909.893.682 (The **Central** of Vietnam)

: +84-909.892.447 (The **South** of Vietnam)

Email : vietnam@ecotek-canada.vn

KEY FEATURE

- Microprocessor control guarantees high reliability
- Equipped with Boost and Buck AVR to stabilize output voltage
- Wide input voltage & frequency range, comply with generator
- Surge protection for both power line and data line (phone / modem)
- Built-in DC start function enables UPS to be started up without AC power supplied
- Super-fast charger shortens the charging time to 2-4 hours
- Auto charging even though the UPS is off
- Auto restart while mains recovery
- USB HID Smart Battery interface enables integration with built-in power management and auto shutdown features of Windows and Mac OS and Linux
- Full protection against over-discharge, overcharge, overload
- Sealed lead-acid, maintenance free battery

SPECIFICATION

MODEL		BLAZER 1200 PRO	BLAZER 2200 PRO
POWER RATING	VAV	1200VA/600W	2200VA/1200W
PRODUCT TOPOLOGY	PRODUCT TOPOLOGY	Line Interactive	
INPUT	Voltage	230VAC	
	Voltage Range	170 ~ 280VAC	
	Frequency	50Hz / 60Hz	
OUTPUT	Voltage	230VAC	
	Voltage Regulation (Batt. Mode)	+/-10%	
	Frequency	50Hz / 60Hz	
	Waveform	Stepped sine wave(Batt. Mode)	
	Frequency Regulation (Batt. Mode)	+/-1Hz	
	Overload capacity	Line mode: 110% +/- 10% after 5 minutes, transfer to fault mode	
	Transfer time	Typical 4-8ms	
BATTERY	Receptacles	NEMA * 6	
	Type	VRLA	
	Configuration	12V7Ah*2	12V9Ah*2
RECHARGE TIME	Recharge time	2-4hours to 90% capacity	
COMMUNICATIONS	USB	USB-HID	
INDICATOR	LCD	LCD display	
DATA LINE SURGE PROTECTION	RJ11 and RJ45 protection	RJ45	
AUDIBLE ALRM	Batt. Mode	Sounding every 10 seconds	
	Low battery	Sounding every 1 second	
	Overload	Sounding every 0.5 second	
	Fault	Continuously sounding	
PROTECTION	Full protection	Deep discharge, Overcharge, and overload protection	
PHYSICAL	Dimension, WxDxH	139 x 364 x 195 mm	
	Net Weight	8.05kg	10.6kg
ENVIRONMENT	Operating Environment	Temperature: 0-40°C Relative Humidity: 0-90%(non-condensing)	
	Noise Level	Less than 40dB	Less than 40dB
BACKUP TIME	For 100W load	40min	50min

Note:

- * All internal batteries are default as STK brand, any other battery brand might be applied without prior notice.
- * Backup time is approximate and may vary with equipment, configuration, battery age, temperature, etc.
- * In the interests of continuous product improvement, all specifications are subject to change without notice.



AUTHORIZED DISTRIBUTER OF SANTAK UPS PRODUCTS IN VIET NAM



Ecotek Canada Promotion Trade Corporation

Address : 3/4 Nguyen Van Thu Str, DaKao ward, District 1, Ho Chi Minh City, Vietnam
 Phone : +84-904.204.849 (The **North** of Vietnam)
 : +84-909.893.682 (The **Central** of Vietnam)
 : +84-909.892.447 (The **South** of Vietnam)
 Email : vietnam@ecotek-canada.vn
 Web : www.ecotek-canada.vn



Technical supports provided by 64 Active Service Points(**A.S.P**)
 licensed by **ECOTEK CANADA**[®]
 covering all 64 provinces and cities of Vietnam